

Giving Shape to Ideas





^{*} Not available at time of launch. Options required for download apps. May not be available in Canada.



bizhub 364e

Growing workloads demand higher productivity – and the bizhub 364e delivers 36 ppm output in crisp B&W, with colour scanning and scalable options that include dual scanning, Super G3 fax, auto-finishing and more — in a compact design with an enhanced touch-and-swipe interface that is as easy as a familiar tablet.

System Overview	
System memory	2,048 MB
System hard disk	250 GB
Interface	10BASE-T/100BASE-TX/1000BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan document feeder (optional)	Up to 100 originals / 5.5 " x 8.5 " to 11" x 17" / 35 -163 gsm Reversing automatic document feeder or dual scan document feeder available
Printable paper size	Scanning/Copying: up to 11" x 17" Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes Banner paper: 11.75" x 47.25" max.
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 1,150 sheets / Max.: 3,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray PC-410 (optional)	2,500 sheets / 8.5" x 11" / 52-256 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, sort, punch, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max.: 50 sheets or 48 sheets + 1 cover sheet (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 150,000 pages/month ¹
Toner lifetime	24,000 pages
Imaging unit lifetime	120,000 pages / 590,000 pages (Drum / Developer)
Power consumption	120 V / 50/60 Hz, less than 1.5 kW (system)
System dimensions	24.2" x 27" x 36.3" (W x D x H)
System weight	Approx. 168.7 lb

		_			
:nn	ıer	Sne	לוחנ	ırat	ions

Copying process	Electrostatic laser copy, tandem, indirect	
Toner system	Simitri™ HD Polymerized Toner	
Print speed (8.5" x 11")	Up to 36 ppm (Portrait)	
Print speed (11" x 17")	Up to 18 ppm (Portrait)	
Autoduplex speed	Up to 36 ppm (Portrait)	
(8.5" x 11")		
1st copy out time	5.3 sec.	
Warm-up time	Approx. 20 sec. ²	
Copy resolution	600 x 600 dpi	
Gradations	256 gradations	
Multi-copy	1-9,999	
Original format	Up to 11" x 17"	
Magnification	25-400% in 0.1% steps, auto zooming	
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image	
	density), proof copy, interrupt mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1	

Printer Specifications

i ilittoi opooliioutiolio	
Print resolution	1800 x 600 dpi, 1200 x 1200 dpi
PDL	PCL 6 (XL 3.0), PCL 5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.2.8 or later UNIX / Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

Scanner Specifications

Scan speed	B&W / Colour: up to 160 opm with optional DF-701
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

Fax Specifications

Fax	Super G3 (optional)
Transmission	Analog, i-Fax, Colour i-Fax, IP-fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to email/FTP/SMB, up to 400 job programs

User Box Specifications

Storable documents	Max.: 3,000 documents or 10,000 pages	
Type of user boxes	Public	
	Personal (with password or authentication)	
	Group (with authentication)	
Type of system boxes	Secure Print, Encrypted PDF, Fax receipt, Fax polling, Annotation	
User box functionality	Reprint, combination, download, sending (email/FTP/SMB and fax), copy box to box	

System Features

Security	ISO 15408 EAL
	IEEE 2600.1
	IP filtering and port blocking
	SSL2, SSL3 and TSL1.0 network communication
	IPsec support
	IEEE 802.1x support
	User authentication
	Authentication log
	Secure print
	Hard disk overwrite (8 standard types)
	Hard disk data encryption (AES 128)
	Memory data auto deletion
	Confidential fax receipt
	Print user data encryption
	Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts
	Active Directory support
	(user name + password + email + SMB folder)
	User function access definition
	Optional Biometric authentication (finger vein scanner)
	Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

Log wariagement during

"Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.

This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

2 Warm-up time may vary depending on the operating environment and usage.

3 Supports x64 only.

Components and Option	S
AU-102 Biometric	Finger vein scanner
authentication	
EK-606 USB I/F kit	USB keyboard connection
EK-607 USB I/F kit	USB keyboard connection, Bluetooth
DF-624	Reversing automatic document feeder, capacity 100 originals
Document feeder	
DF-701	Dual scan automatic document feeder, capacity 100 originals
Document feeder	
DK-510 Copier desk	Provides storage space for print media and other materials
FK-508 Fax board	Super G3 fax, digital fax functionality, lines 3 & 4 support
FK-511 Fax board	Super G3 fax, digital fax functionality
FS-533 Staple finisher	50-sheet stapling, 500 sheets max. output
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output
FS-534 + SD-511	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	3,300 sheets max. output
ID card reader	Various ID card technologies
JS-506 Job separator	Separation for fax output, etc.
KH-102	To place USB keyboard
Keyboard holder	
KP-101 10-Key pad	For use instead of touchscreen
LK-101 v3	Web browser
Web browser	
LK-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	
LK-104 v3	Provides voice guidance functions
Voice guidance	O I. I. I. DDF
LK-105 v3 OCR text recognition	Searchable PDF
LK-106	Supports native barcode printing
Barcode fonts	Supports flative barcode printing
LK-107	Supports native Unicode printing
Unicode fonts	cappoint matrix of modulo printing
LK-108	Supports native OCR A and B font printing
OCR A and B fonts	
LK-110 Enhanced	Generates various file formats including DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint® Client	
MK-728 Mount kit	Installation kit for FK-508 fax board
MK-735 Mount kit	Installation kit for ID card reader
OC-511 Original cover	Cover instead of auto document feeder
PC-110	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm
Universal tray (x1)	5 CH 0 CH 44H 47H 0 500 ch 1 50 0 CO 1 1
PC-210	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm
Universal tray (x2) PC-410	8.5" x 11", 2,500 sheets, 52-256 gsm
Large capacity tray	6.5 X 11 , 2,500 Sileets, 52-250 ysiii
PK-519 Punch kit	2/3-hole punching, autoswitching
for FS-533	275 Hole purioning, autoswitching
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-534	2.5 note parterning, automating
SC-508 Security kit	Copy Guard function (2x required when optional DF-701 is installed)
UK-204	Memory extension for i-Options
i-Option memory	· · · · · · · · · · · · · · · · · · ·
UK-208 Wireless LAN	Wireless LAN to network connector
UK-209 DS board for	bizhub RA when machine is equipped with DF-624
bizhub RA	
WT-506 Working table	Authentication device placement





KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. 5875 Explorer Drive, Suite 100, Mississauga, ON L4W 0E1











