

# Giving Shape to Ideas



Up to 22 ppm print/copy output to keep pace with rising demands

Colour display with quick tablet-like interface

Touchscreen for simple control and 3rd-party software integration

Standard web browser to support web-based apps

Built-in Emperon® print system, universal printer drivers

Simitri® HD polymerized toner for high-resolution imaging

Standard 250 GB HDD for on-board document storage

Meets ISO 15408 and IEEE 2600.1 security standards

Power-saving design with quick recovery from sleep mode

3,600-sheet maximum capacity, tab printing support, carbon-copy printing

Advanced authentication, secure print release, remote firmware updates

Options for booklet-making, stapling, hole-punch, and more

Downloadable apps to help you work faster and smarter

i-Options to add functions for working more efficiently

Low power consumption to cut costs

Mobile printing support (AirPrint, Google Cloud Print, NFC)

# bizhub C227

COLOUR MID-VOLUME MULTIFUNCTION PRINTER

mfp





# bizhub C227

As easy as a familiar tablet, the enhanced touch-and-swipe interface of the bizhub C227 helps make you more productive — with 22 ppm output in high-resolution colour, scanning up to 45 originals per minute, 3,600-sheet maximum paper capacity and economical, high-value performance.

#### **System Overview**

| System Overview                                |  |
|--|--|
| System memory                                  | 4 GB (when UK-211 is installed)  |
| System hard disk                               | 250 GB   |
| Interface                                      | 10BASE-T/100BASE-TX/1000BASE-T Ethernet, USB 2.0                                 |
| Network protocols                              | TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS                             |
| Frame types                                    | Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP                       |
| Reversing automatic document feeder (optional) | Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 50-128 gsm                      |
| Printable paper size                           | Scanning/Copying: up to 11" x 17"  Printing: up to 11" x 17"  Custom paper sizes |
| Printable paper weight                         | 60-220 gsm   |
| Paper input capacity                           | Standard: 1,100 sheets / Max.: 3,600 sheets                                      |
| Tray 1   | 500 sheets / 5.5" x 8.5" to 8.5" x 14" / 60-220 gsm                              |
| Tray 2   | 500 sheets / 5.5" x 8.5" to 11" x 17" / 60-220 gsm                               |
| Tray 3 (optional)                              | 500 sheets / 5.5" x 8.5" to 11" x 17" / 60-220 gsm                               |
| Tray 4 (optional)                              | 2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 60-220 gsm                          |
| Large capacity tray<br>PC-413 (optional)       | 2,500 sheets / 8.5" x 11" / 60-220 gsm   |
| Manual bypass                                  | 100 sheets / 4" x 6" to 11" x 17" / custom paper sizes / 60-220 gsm              |
| Automatic duplexing                            | 5.5" x 8.5" to 11" x 17" / 60-220 gsm  |
| Finishing modes                                | Offset, group, sort, punch, half-fold, tri-fold, booklet                         |
| Output capacity                                | Max. with finisher: 3,300 sheets<br>Max. without finisher: 250 sheets            |
| Stapling (optional)                            | Max.: 50 sheets or 48 sheets + 1 cover sheet (up to 209 gsm)                     |
| Stapling output capacity                       | Max.: 1,000 sheets   |
| Tri-fold (optional)                            | Up to 3 sheets   |
| Tri-fold capacity                              | Max.: 30 sheets (tray)   |
| Booklet (optional)                             | Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)                     |
| Booklet output capacity                        | Max.: 100 sheets (tray)  |
| Copy/print volume                              | Max.: 100,000 pages/month <sup>1</sup>   |
| Toner lifetime                                 | 23,000 pages   |
| Imaging unit lifetime                          | 85,000 pages / 600,000 pages (Drum / Developer)                                  |
| Power consumption                              | 120 V / 50/60 Hz, less than 1.5 kW (system)                                      |
| System dimensions                              | 23.0" x 26.0" x 28.9" (W x D x H)  |
| System weight                                  | Approx. 124.6 lb   |
|  |  |

|    |     |      | _  |    |              |     |     |    |
|----|-----|------|----|----|--------------|-----|-----|----|
| 'n | nia | ar ' | Сn | ec | ifi <i>r</i> | rat | ini | 10 |
|    |     |      |    |    |              |     |     |    |

| Copying process          | Electrostatic laser copy, tandem   |  |  |
|--------------------------|--|--|--|
| Toner system             | Simitri® HD Polymerized Toner  |  |  |
| Print speed (8.5" x 11") | Up to 22 ppm (Portrait)  |  |  |
| Print speed (11" x 17")  | Up to 14 ppm   |  |  |
| Auto-duplex speed        | Up to 22 ppm (Portrait)  |  |  |
| (8.5" x 11")             |  |  |  |
| 1st copy out time        | <b>B&amp;W:</b> 6.8 sec. / <b>Colour:</b> 8.4 sec.   |  |  |
| Warm-up time             | Approx. 20 sec. <sup>2</sup>   |  |  |
| Copy resolution          | 600 dpi x 600 dpi  |  |  |
| Gradations               | 256 gradations   |  |  |
| Multi-copy               | 1-9,999  |  |  |
| Original format          | Up to 11" x 17"  |  |  |
| Magnification            | 25-400% in 0.1% steps, auto zooming  |  |  |
| Copy functions           | Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, colour mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1 |  |  |

### **Printer Specifications**

| Print resolution  | 1800 dpi (equivalent) x 600 dpi   |  |  |
|-------------------|---|--|--|
| PDL               | PCL 6 (XL 3.0), PCL 5c, PostScript 3 (ver. 3016), XPS   |  |  |
| Operating systems | Windows (x32/x64): XP / Vista / 7 / 8 / 10<br>Windows Server (x32/x64): 2003 / 2008 / 2008 R2³ / 2012³<br>Macintosh OS X 10.2.8 or later<br>UNIX / Linux / Citrix                                   |  |  |
| Printer fonts     | 80 PCL Latin, 137 PostScript 3  |  |  |
| Print functions   | Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print |  |  |

# **Scanner Specifications**

| Scan speed        | B&W / Colour: up to 45 opm  |
|-------------------|---|
| Scan resolution   | Max.: 600 dpi x 600 dpi   |
| Scan modes        | Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan   |
| File formats      | JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional) |
| Scan destinations | 2,100 (shared with fax), LDAP support   |
| Scan functions    | Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview  |
|                   |   |

# **Fax Specifications**

| Fax          | Super G3 (optional)<br>Analog, i-Fax, Colour i-Fax, IP-Fax   |  |  |
|--------------|--|--|--|
| Transmission |  |  |  |
| Resolution   | Max.: 600 dpi x 600 dpi (ultra-fine)   |  |  |
| Compression  | MH, MR, MMR, JBIG  |  |  |
| Modem        | Up to 33.6 Kbps  |  |  |
| Destinations | 2,100 (single + group)   |  |  |
| Functions    | Polling, time shift, PC-fax, receipt to confidential box, receipt to email/FTP/SMB, up to 400 job programs |  |  |

# **User Box Specifications**

| Storable documents     | Max.: 3,000 documents or 10,000 pages  |
|------------------------|--|
| Type of user boxes     | Public   |
|                        | Personal (with password or authentication)                                       |
|                        | Group (with authentication)  |
| Type of system boxes   | Secure print, encrypted PDF, fax receipt, fax polling, annotation                |
| User box functionality | Reprint, combination, download, sending (email/FTP/SMB and fax), copy box-to-box |
|                        | сору вох-то-вох  |

# **System Features**

| Security   | ISO 15408 EAL   |  |  |  |  |
|------------|---|--|--|--|--|
|            | IEEE 2600.1   |  |  |  |  |
|            | IP filtering and port blocking  |  |  |  |  |
|            | SSL2, SSL3 and TSL1.0 network communication   |  |  |  |  |
|            | IPsec support   |  |  |  |  |
|            | IEEE 802.1x support User authentication   |  |  |  |  |
|            |   |  |  |  |  |
|            | Authentication log Secure print Hard disk overwrite (8 standard types) Hard disk data encryption (AES 128) Memory data auto deletion Confidential fax reception |  |  |  |  |
|            |   |  |  |  |  |
|            |   |  |  |  |  |
|            |   |  |  |  |  |
|            |   |  |  |  |  |
|            |   |  |  |  |  |
|            | Print user data encryption<br>Copy protection (Copy Guard, Password Copy) optional  |  |  |  |  |
|            |   |  |  |  |  |
| Accounting | Up to 1,000 user accounts   |  |  |  |  |
|            | Active Directory support  |  |  |  |  |
|            | (user name + password + email + SMB folder)   |  |  |  |  |
|            | User function access definition   |  |  |  |  |
|            | Optional Biometric authentication (finger vein scanner)   |  |  |  |  |
|            | Optional ID card authentication (ID card reader)  |  |  |  |  |
| Software   | PageScope Net Care Device Manager   |  |  |  |  |
|            | PageScope Data Administrator  |  |  |  |  |
|            | PageScope Box Operator  |  |  |  |  |
|            | Print Status Notifier   |  |  |  |  |
|            | Driver Packaging Utility  |  |  |  |  |
|            | Log Management Utility  |  |  |  |  |
|            |   |  |  |  |  |

<sup>1</sup> Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis.

This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

2 Warm-up time may vary depending on the operating environment and usage.

3 Supports x64 only.

| <b>Components and Options</b>  | 8  |  |  |
|--------------------------------|--|--|--|
| AU-102 Biometric               | Finger vein scanner  |  |  |
| authentication                 |  |  |  |
| AU-205H Universal              | Various ID card technologies   |  |  |
| ID card reader                 |  |  |  |
| EK-608 USB I/F kit             | USB keyboard connection  |  |  |
| EK-609 USB I/F kit             | USB keyboard connection, Bluetooth                                       |  |  |
| DF-628                         | Reversing automatic document feeder, capacity 100 originals              |  |  |
| Document feeder                |  |  |  |
| DK-514 Copier desk             | Provides storage space for print media and other materials               |  |  |
| FK-513 Fax board               | Super G3 fax, digital fax functionality                                  |  |  |
| FS-533 Staple finisher         | 50-sheet stapling, 500 sheets max. output                                |  |  |
| 1 0-000 otapie iiiioliei       | (requires MK-602 + MK-603)   |  |  |
| FS-534 Staple finisher         | 50-sheet stapling, 3,300 sheets max. output                              |  |  |
|                                | (requires RU-514 + MK-603)   |  |  |
| FS-534 + SD-511                | 50-sheet staple finisher, 20-sheet booklet finisher,                     |  |  |
| Booklet finisher               | 3,300 sheets max. output (requires RU-514)                               |  |  |
| JS-506 Job separator           | Separation for fax output, etc.  |  |  |
| KH-102                         | To place USB keyboard  |  |  |
| Keyboard holder                |  |  |  |
| KP-101 10-Key pad              | For use instead of touchscreen   |  |  |
| LK-102 v3                      | PDF/A, PDF encryption, digital signature                                 |  |  |
| PDF enhancements               |  |  |  |
| LK-104 v3                      | Provides voice guidance functions  |  |  |
| Voice guidance                 |  |  |  |
| LK-105 v4                      | Searchable PDF   |  |  |
| OCR text recognition           |  |  |  |
| LK-106                         | Supports native barcode printing   |  |  |
| Barcode fonts                  |  |  |  |
| LK-107                         | Supports native Unicode printing   |  |  |
| Unicode fonts                  |  |  |  |
| LK-108                         | Supports native OCR A and B font printing                                |  |  |
| OCR A and B fonts              |  |  |  |
| LK-110 v2 Enhanced             | Generates various file formats incl. DOCX, XLSX and combines             |  |  |
| image support                  | LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)       |  |  |
| LK-111                         | Print data compression for reduced network impact                        |  |  |
| ThinPrint® Client              |  |  |  |
| MK-602 Mount kit               | Installation kit required for FS-533                                     |  |  |
| MK-603 Mount kit               | Installation kit required for FS-533, FS-534, FS-534 + SD-511 and JS-506 |  |  |
| MK-735 Mount kit               | Installation kit for ID card reader                                      |  |  |
| OC-514 Original cover          | Cover instead of auto document feeder                                    |  |  |
| PC-114                         | 5.5" x 8.5" to 11" x 17", 500 sheets, 60-220 gsm                         |  |  |
| Universal tray (x1)            |  |  |  |
| PC-214                         | 5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 60-220 gsm                     |  |  |
| Universal tray (x2)            |  |  |  |
| PC-414                         | 8.5" x 11", 2,500 sheets, 60-220 gsm                                     |  |  |
| Large capacity tray            |  |  |  |
| PK-519 Punch kit               | 2/3-hole punching, autoswitching   |  |  |
| for FS-533                     | 0.01   |  |  |
| PK-520 Punch kit<br>for FS-534 | 2/3-hole punching, autoswitching   |  |  |
| RU-514 Relay unit              | Required for installation of FS-534                                      |  |  |
| UK-211                         | 2 GB memory expansion, required for most i-Options, registered           |  |  |
|                                | overlay, and concurrent use of web browser and certain other             |  |  |
|                                | functions, including stamp print, watermark, date/time print,            |  |  |
|                                | header/footer, image overlay, and management number                      |  |  |
| UK-212 Wireless LAN            | Wireless LAN to network connector  |  |  |
| WT-506 Working table           | Authentication device placement  |  |  |
|                                |  |  |  |



KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. 5875 Explorer Drive, Suite 100, Mississauga, ON L4W 0E1

www.konicaminolta.ca





